

## COVALENCE<sup>®</sup> S1135 ADHESIVE TAPE

<b>Characteristics:</b>	High temperature adhesive tape on rolls with release plastic.								
<b>Applications:</b>	Used in combinations with PPS120, HTLP-PP-DA, DIRAX-PP as tie-layer onto the 3LPP line coating.								
<b>Product description:</b>	<b>S1135-XXXxYYYxZZM-PL-RL</b> XXX = Width in mm YYY = Thickness in mm ZZ = Length in m								
<b>Material properties:</b>	Typical Softening point : 155°C (311°F) Typical Shear strength: 0.13 N/mm <sup>2</sup> @ 23°C (73.4°F) acc ISO21809-3 Typical Peel strength: 0.7 N/mm @ 23°C (73.4°F) acc ISO21809-3								
<b>Dimensions:</b>	Width: 30 mm (1.181"), 50 mm (1.969"), 75 mm (3") Thickness: 1 mm (0.039") Length per roll: 30 m (98 ft), 90 m (295 ft)								
<b>Product printing &amp; labeling:</b>	No printing. Standard box labeling: Covalence Description, Part Number, Lotnumber, Quantity								
<b>Ordering info:</b>	S1135 rolls are packed in a box <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>S1135-</th> <th>Quantity per box</th> </tr> </thead> <tbody> <tr> <td>30X1X90M-PL-RL(C7)</td> <td>7</td> </tr> <tr> <td>50X1X30M-PL-RL(C6)</td> <td>6</td> </tr> <tr> <td>75X1X30M-PL-RL(C5)</td> <td>5</td> </tr> </tbody> </table>	S1135-	Quantity per box	30X1X90M-PL-RL(C7)	7	50X1X30M-PL-RL(C6)	6	75X1X30M-PL-RL(C5)	5
S1135-	Quantity per box								
30X1X90M-PL-RL(C7)	7								
50X1X30M-PL-RL(C6)	6								
75X1X30M-PL-RL(C5)	5								

### Information

<b>Documentation</b>	Extensive information is available on our web-site. Application instructions and other documentation can be obtained by contacting our head office, from our local distributor or by sending an email to <a href="mailto:info@sealforlife.com">info@sealforlife.com</a>
<b>Certified staff</b>	Application of the described coating system should be carried out by certified personnel.